

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifiers**Article No. (manufacturer/supplier) 680-0181  
Identification of the substance or mixture REDOCRYL HS 181 VOC matt  
2K HS Acrylklarlack  
MV 3:1 mit Härter 200**1.2. Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses:**

2 component clear coat for car repair painting

**1.3. Details to the supplier providing the material safety data sheet****Producer:****FEYCOLOR GmbH**Maxhuettenstraße 6,  
93055 Regensburg,  
GermanyTel.: +49 (0) 941/ 60497-0  
Fax.: +49 (0) 941/ 60497-30  
info@feycolor.com[<www.feycolor.com>](http://www.feycolor.com)**Office hours:**Monday - Thursday: 08:00 - 12:00 and 13:00 - 16:00  
Friday: 08:00 - 12:00Email: sd@feycolor.com  
www.feycolor.com <http://www.feycolor.com>**1.4. Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM)****SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.

**Classification according to Directive 67/548/EEC or 1999/45/EC**

This mixture is classified as hazardous according to 1999/45/EC.

R10	Flammable
R52-53	Harmful to aquatic life. May cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]****Hazard pictograms****Warning****Hazard statements**H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof electrical equipment.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308 + P313 IF exposed or concerned: Get medical advice/attention.
- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container to industrial incineration plant.
- P102 Keep out of reach of children.

**contains:**

n-butyl acetate

**Supplemental Hazard information (EU)**

- EUH066 Repeated exposure may cause skin dryness or cracking.
- EUH208 Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate; Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; 2,3-Epoxypropyl neodecanoate. May produce an allergic reaction.

**Labelling (67/548/EEC or 1999/45/EC)**

**Hazard statements**

- 10 Flammable
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

**Precautionary statements**

- 24 Avoid contact with skin.
- 38 In case of insufficient ventilation, wear suitable respiratory equipment.
- 51 Use only in well-ventilated areas.
- 61 Avoid release to the environment. Refer to special instructions/safety data sheet.
- 23 Do not breathe vapour.

**contains:**

n.a.

**Special provisions concerning the labelling of certain mixtures**

- 99 Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat; Methyl-(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat; 2,3-EPOXYPROPYLNEODECANOAT. May produce an allergic reaction.

2.3. Other hazards

**SECTION 3: Composition / information on ingredients**

3.2. Mixtures

**Product description / chemical characterization**

**Description** Gemisch aus nachfolgend angeführten Stoffen mit ungefährlichen Beimengungen

**Hazardous ingredients**

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

EC No.	REACH No.	Wt %
CAS No.	Chemical name	Remark
INDEX No.	classification	
255-437-1	01-2119491304-40	
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate Skin Sens. 1 H317 / Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	0,5 - 1
280-060-4		
82919-37-7	Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate Skin Sens. 1 H317 / Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	< 0,5
204-658-1		
123-86-4	n-butyl acetate	25 - 50
607-025-00-1	Flam. Liq. 3 H226 / STOT SE 3 H336	

Article No.: 680-0181 REDOCRYL HS 181 VOC matt  
 Print date: 08.06.2015 Revision date: 02.06.2015  
 Version: 1.0 Issue date: 02.06.2015

EN  
 Page 3 / 9

247-979-2 26761-45-5	01-2119431597-33 2,3-Epoxypropyl neodecanoate Skin Sens. 1 H317 / Aquatic Chronic 2 H411 / Muta. 2 H341	0,5 - 1
918-668-5 64742-95-6	01-2119455851-35 Solvent naphtha (petroleum), light arom. Flam. Liq. 3 H226 / STOT SE 3 H335 / Aquatic Chronic 2 H411 / Asp. Tox. 1 H304 / STOT SE 3 H336	5 - 10
215-535-7 1330-20-7	01-2119488216-32 xylene Flam. Liq. 3 H226 / Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Asp. Tox. 1 H304 / STOT RE 2 H373 / STOT SE 3 H335	2,5 - 5

**Classification according to Directive 67/548/EEC or 1999/45/EC**

EC No. CAS No. INDEX No.	REACH No. Chemical name classification	Wt % Remark
204-658-1 123-86-4 607-025-00-1	01-2119485493-29 n-butyl acetate R10 / R66 / R67	25 - 50
918-668-5 64742-95-6	01-2119455851-35 Lösungsmittel, C9 Kohlenwasserstoffe, Aromaten R10 / Xi; R37 / N; R51-53 / Xn; R65 / R66 / R67	5 - 10
215-535-7 1330-20-7	01-2119488216-32 xylene, mixture of isomers R10 / Xn; R20/21-48/20-65 / Xi; R36/37/38	2,5 - 5
255-437-1 41556-26-7	01-2119491304-40 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat R43 / N; R50-53	0,5 - 1
247-979-2 26761-45-5	01-2119431597-33 2,3-EPOXYPROPYLNEODECANOAT R43 / N; R51-53 / Muta.Cat.3; R68	0,5 - 1
265-185-4 64742-82-1	01-2119458049-33 Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha R10 / N; R51-53 / Xn; R65 / R66 / R67	0,5 - 1
407-000-3 127519-17-9 607-281-00-4	01-0000015648-61 reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H- benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl] propionates N; R51-53	< 0,5
280-060-4 82919-37-7	Methyl-(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat R43 / N; R50-53	< 0,5

**Additional information**

Full text of R-phrases: see section 16.

Full text of H-phrases: see section 16.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

- 4.2. **Most important symptoms and effects, both acute and delayed**  
In all cases of doubt, or when symptoms persist, seek medical advice.
- 4.3. **Indication of any immediate medical attention and special treatment needed**

### SECTION 5: Firefighting measures

- 5.1. **Extinguishing media**  
**Suitable extinguishing media:**  
alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)  
**Extinguishing media which must not be used for safety reasons:**  
strong water jet
- 5.2. **Special hazards arising from the substance or mixture**  
Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.
- 5.3. **Special protective equipment for firefighters:**  
Provide a conveniently located respiratory protective device.  
**Additional information**  
Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

### SECTION 6: Accidental release measures

- 6.1. **Personal precautions, protective equipment and emergency procedures**  
Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.
- 6.2. **Environmental precautions**  
Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.
- 6.3. **Methods and material for containment and cleaning up**  
Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.
- 6.4. **Reference to other sections**  
Observe protective provisions (see chapter 7 and 8).

### SECTION 7: Handling and storage

- 7.1. **Precautions for safe handling**  
**Advices on safe handling**  
Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.  
**Precautions against fire and explosion:**  
Vapours are heavier than air. Vapours form explosive mixtures with air.
- 7.2. **Conditions for safe storage, including any incompatibilities**  
**Requirements for storage rooms and vessels**  
Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".  
**Hints on joint storage**  
Keep away from strongly acidic and alkaline materials as well as oxidizers.  
**Further information on storage conditions**  
Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect

from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

- 7.3. **Specific end use(s)**  
 Observe technical data sheet.

**SECTION 8: Exposure controls/personal protection**

- 8.1. **Control parameters**  
**Occupational exposure limit values:**  
 n-butyl acetate  
 INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4  
 MEL/OES, TWA: 724 mg/m<sup>3</sup>; 150 ppm  
 MEL/OES, STEL: 966 mg/m<sup>3</sup>; 200 ppm

**Additional information**  
 TWA : long-term occupational exposure limit value  
 STEL : short-term occupational exposure limit value  
 Ceiling : peak limitation

- 8.2. **Exposure controls**  
 Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

**Occupational exposure controls**

**Respiratory protection**  
 If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

**Hand protection**  
 For prolonged or repeated handling the following glove material must be used: solventresistant Latex gloves  
 Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.  
 Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374  
 Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye protection**  
 Wear closely fitting protective glasses in case of splashes.

**Protective clothing**  
 Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

**Protective measures**  
 After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**  
 Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

**SECTION 9: Physical and chemical properties**

- 9.1. **Information on basic physical and chemical properties**

**Appearance:**  
**Physical state**                      liquid  
**Colour**                                see productname  
**Odour**                                 typical

Safety relevant basis data	Unit	Method	Remark
Flash point:	23 °C		
Ignition temperature in °C:	370 °C		
Lower explosion limit:	1,2 Vol-%		
Upper explosion limit:	7,5 Vol-%		
Vapour pressure at 20 °C:	10,70 mbar		
Density at 20 °C:	1,05 g/cm <sup>3</sup>		
Water solubility (g/L):	insoluble		
pH at 20 °C:	n.a.	Wt %	
Viscosity at 20 °C:	160 s 4 mm	DIN 53211	
Solvent separation test (%):	< 3 %	ADR/RID	
Solid content (%):	52 Wt %		
solvent content:			

**Organic solvents:** 47,70 Wt %  
**Water:** 0,00 Wt %

9.2. **Other information**

**SECTION 10: Stability and reactivity**

10.1. **Reactivity**

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

**SECTION 11: Toxicological information**

No data on preparation itself available.

11.1. **Information on toxicological effects**

**Acute toxicity**

n-butyl acetate  
 oral, LD50, Rat:

**Irritant and corrosive effects**

Toxicological data are not available.

**Sensitisation**

Toxicological data are not available.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Toxicological data are not available.

**Specific target organ toxicity**

Toxicological data are not available.

**Aspiration hazard**

Toxicological data are not available.

**Practical experience/human evidence**

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

**Overall Assessment on CMR properties**

The ingredients in this preparation do not meet the criteria for classification as CMR category 1 or 2 according to 67/548/EEC.

There is no information available on the preparation itself . The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

**SECTION 12: Ecological information**

**overall evaluation**

There is no information available on the preparation itself .  
 Do not allow to enter into surface water or drains.

12.1. **Toxicity**

No information available.

**Long-term Ecotoxicity**

Toxicological data are not available.

**12.2. Persistence and degradability**

Toxicological data are not available.

**12.3. Bioaccumulative potential**

Toxicological data are not available.

**Bioconcentration factor (BCF)**

Toxicological data are not available.

**12.4. Mobility in soil**

Toxicological data are not available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects****SECTION 13: Disposal considerations****13.1. Waste treatment methods****Appropriate disposal / Product Recommendation**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**List of proposed waste codes/waste designations in accordance with EWC**

080111 waste paint and varnish containing organic solvents or other dangerous substances

**packaging****Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information****14.1. UN number**

1263

**14.2. UN proper shipping name**Land transport (ADR/RID): Paint  
Sea transport (IMDG): PAINT  
Air transport (ICAO-TI / IATA-DGR): Paint**14.3. Transport hazard class(es)**Land transport (ADR/RID): "No good according class 3"  
containers > 450 l = class 3  
Sea transport (IMDG)  
for packages < 30 litres: 3  
Transport in accordance with 2.3.2.5 of the IMDG Code.  
Air transport (ICAO-TI / IATA-DGR): 3**14.4. Packing group**

III

**14.5. Environmental hazards**Land transport (ADR/RID) n.a.  
Marine pollutant n.a.**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Additional information****Land transport (ADR/RID)**tunnel restriction code D/E  
SONDERVORSCHRIFT 640E

**Sea transport (IMDG)**

EmS-No. F-E, S-E

14.7. **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**  
 not applicable

**SECTION 15: Regulatory information**

15.1. **Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).**

VOC-value (in g/L) ISO 11890-2: 458  
 VOC-value (in g/L) ASTM D 2369: 458

**according to EU-regulation 2004/42/EC (appendix II)**

EU limit value for this product (cat. (Cat. B/e)): 840 g/l (2007)/840 g/l (2010).  
 This product contains max 463 g/l VOC.

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
 Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

**Other regulations, restrictions and prohibition regulations**

15.2. **Chemical Safety Assessment**

**For the following substances of this preparation a chemical safety assessment has been carried out:**

EC No. CAS No.	Chemical name	REACH No.
204-658-1 123-86-4	n-butyl acetate	01-2119485493-29
407-000-3 127519-17-9	reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl] propionates	01-0000015648-61
255-437-1 41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat	01-2119491304-40
247-979-2 26761-45-5	2,3-EPOXYPROPYLNEODECANOAT	01-2119431597-33
918-668-5 64742-95-6	Lösungsmittel, C9 Kohlenwasserstoffe, Aromaten	01-2119455851-35
215-535-7 1330-20-7	xylene, mixture of isomers	01-2119488216-32
265-185-4 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha	01-2119458049-33

**SECTION 16: Other information**

**Relevant R-and H-phrases (Number and full text):**

Skin Sens. 1 / H317	respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic life.
Aquatic Chronic 1 / H410	Hazardous to the aquatic environment	Very toxic to aquatic life with long lasting effects.
Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Muta. 2 / H341	Germ cell mutagenicity	Suspected of causing genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
STOT SE 3 / H335	Specific target organ toxicity (single exposure)	May cause respiratory irritation.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT RE 2 / H373	Specific target organ toxicity (repeated exposure)	May cause damage to organs (or state all organs affected, if known) through prolonged or

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) No 453/2010**

Article No.: 680-0181 REDOCRYL HS 181 VOC matt  
 Print date: 08.06.2015 Revision date: 02.06.2015  
 Version: 1.0 Issue date: 02.06.2015

R10		repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
R66		Flammable
R67		Repeated exposure may cause skin dryness or cracking.
N; R51-53	Dangerous for the environment	Vapours may cause drowsiness and dizziness.
R43		Toxic to aquatic life. May cause long-term adverse effects in the aquatic environment.
N; R50-53	Dangerous for the environment	May cause sensitization by skin contact.
Muta.Cat.3; R68	Mutagenic Cat. 3 (Mut. Cat. 3)	Very toxic to aquatic life. May cause long-term adverse effects in the aquatic environment.
Xi; R37	Irritant	Possible risk of irreversible effects.
Xn; R65	Harmful	Irritating to respiratory system.
Xn; R20/21-48/20-65	Harmful	Harmful: may cause lung damage if swallowed.
		Harmful by inhalation and in contact with skin.
		Harmful: danger of serious damage to health by prolonged exposure through inhalation.
		Harmful: may cause lung damage if swallowed.
Xi; R36/37/38	Irritant	Irritating to eyes, respiratory system and skin.

**Additional information**

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.