

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Steinschlag-Unterbodenschutz hellgrau 1l

Print date: 02.07.2020

Product code: 5550018

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

JMC Steinschlag-Unterbodenschutz hellgrau 1l

Further trade names

JMC Steinschlag-Unterbodenschutz schwarz 1l (JM-Nr. 555 00 16)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

SU21 Consumer uses: Private households (= general public = consumers)

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

PC9a Coatings and paints, thinners, paint removers

Plating agent

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Johannes J. Matthies GmbH & Co. KG
Street: Hammerbrookstr. 97
Place: D-20097 Hamburg
Telephone: + 49 (0) 40 2 37 21-0
e-mail: info@matthies.de
Internet: www.matthies.de

Supplier

Company name: Larsson UK Ltd.
Street: 7 Alpha Court, Phoenix Parkway
Place: GB-NN17 5DP Corby
Telephone: + 44 1536 265633
e-mail: info@larsson.uk.com
Internet: www.larsson.uk.com

1.4. Emergency telephone number: + 44 1536 265633

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Steinschlag-Unterbodenschutz hellgrau 1l

Print date: 02.07.2020

Product code: 5550018

Page 2 of 10

Hazard components for labelling

ethyl acetate

Hydrocarbons

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Signal word:

Danger

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat. No Smoking.
P260	Do not breathe vapour.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P501	Dispose of waste according to applicable legislation.

2.3. Other hazards

@ES04.B001378: not applicable

@ES04.B001379: not applicable

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture consisting of the following substances with harmless admixtures.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Steinschlag-Unterbodenschutz hellgrau 1l

Print date: 02.07.2020

Product code: 5550018

Page 3 of 10

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
141-78-6	ethyl acetate			20 - < 25 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
	Hydrocarbons			12,5 - < 20 %
	927-510-4		01-2119475515-33	
	Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H315 H336 H304 H411			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%			5 - < 10 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			5 - < 10 %
	920-750-0		01-2119473851-33	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411			
	Hydrocarbons, C9, aromatics			< 2,5 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411			

Full text of H and EUH statements: see section 16.

Further Information

The benzene content (EINECS No. 200-753-7) in individual components is less than 0.1% (Annotation P Annex I of Directive 67/548/EEC).

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

If unconscious place in recovery position and seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Provide fresh air. Rinse mouth immediately and drink plenty of water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water mist, Carbon dioxide (CO₂), Extinguishing powder

In case of major fire and large quantities: Water spray jet, alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Steinschlag-Unterbodenschutz hellgrau 11

Print date: 02.07.2020

Product code: 5550018

Page 4 of 10

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Gases/vapours, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use suitable breathing apparatus. Use personal protection equipment. Remove persons to safety.

6.2. Environmental precautions

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Provide adequate ventilation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Ensure that the workplace is well ventilated/has an extractor system.
Avoid aerosol formation.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.
Take precautionary measures against static discharges.
Use appropriate respiratory protection.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Store in a cool dry place.

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL

Additional advice on limit values

The lists valid during compilation serve as a basis.

8.2. Exposure controls

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Steinschlag-Unterbodenschutz hellgrau 1l

Print date: 02.07.2020

Product code: 5550018

Page 5 of 10



Appropriate engineering controls

See section 7. Additional information on plant design:

Protective and hygiene measures

Keep away from food, drink and animal feedingstuffs.
 Remove contaminated, saturated clothing immediately.
 Wash hands before breaks and after work.
 Do not breathe gas/fumes/vapour/spray.
 Avoid contact with skin.
 Avoid contact with eyes.

Eye/face protection

Suitable eye protection: Wear eye/face protection.

Hand protection

Wear suitable gloves.

Suitable material: Butyl caoutchouc (butyl rubber)
 Thickness of the glove material 0,4 mm

The required protective gloves have to be specified by the glove material and the penetration time of the glove material depending on strength and duration of dermal exposition.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection

Unnecessary where room is well ventilated.
 Use a respiratory filter unit in the event of brief or low exposure. A respirator with an independent oxygen supply must be used in the event of more intensive or longer exposure.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	black / light grey
Odour:	characteristic

Test method

pH-Value:	not determined
-----------	----------------

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	80 °C
Flash point:	-1 °C

Flammability

Solid:	not applicable
Gas:	not applicable

Explosive properties

The product is not explosive, but explosive vapour/air mixtures may form.

Lower explosion limits:	0,8 vol. %
Upper explosion limits:	8,0 vol. %

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Steinschlag-Unterbodenschutz hellgrau 11

Print date: 02.07.2020

Product code: 5550018

Page 6 of 10

Ignition temperature:	450 °C
Auto-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined
Vapour pressure: (at 20 °C)	85 hPa
Density (at 20 °C):	1,02 g/cm ³
Water solubility:	Immiscible or difficult to mix.
Partition coefficient:	not determined
Viscosity / dynamic:	not determined
Flow time: (at 20 °C)	17 s (ISO 6mm)
Vapour density:	not determined
Evaporation rate:	not determined
Solvent content:	EU-VOC: 540,6 g/l EU-VOC in %: 53

9.2. Other information

Solid content: 47,3%

Odour threshold: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Steinschlag-Unterbodenschutz hellgrau 1l

Print date: 02.07.2020

Product code: 5550018

Page 7 of 10

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
141-78-6	ethyl acetate			
	oral	LD50 > 18000 mg/kg	Rabbit	
	dermal	LD50 5620 mg/kg	Rat	
	inhalation (4 h) aerosol	LC50 1,6 mg/l	Rat	
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%			
	oral	LD50 > 5840 mg/kg	Rat	
	dermal	LD50 > 2920 mg/kg	Rabbit	
	inhalation (4 h) aerosol	LC50 > 25,2 mg/l	Rat	
	Hydrocarbons, C9, aromatics			
	oral	LD50 3592 mg/kg	Rat	
	dermal	LD50 3160 mg/kg	Rabbit	

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (ethyl acetate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity**

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%				
	Acute fish toxicity	LC50 11,4 mg/l	96 h	Fisch	
	Acute algae toxicity	ErC50 30 - 100 mg/l	72 h	Algae	
	Acute crustacea toxicity	EC50 3 mg/l	48 h	Daphnia magna (Big water flea)	
	Hydrocarbons, C9, aromatics				
	Acute fish toxicity	LC50 9,2 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 2,75 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 3,2 mg/l	48 h	Daphnia magna (Big water flea)	

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Steinschlag-Unterbodenschutz hellgrau 1l

Print date: 02.07.2020

Product code: 5550018

Page 8 of 10

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter groundwater, bodies of water or the sewage system in an undiluted condition or larger quantities.

Drinking water is already threatened by minor quantities seeping into the groundwater.

Toxic to aquatic life. Toxic to fish.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Should not be disposed of together with household waste. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1139
<u>14.2. UN proper shipping name:</u>	Coating solution
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Marine transport (IMDG)

<u>14.1. UN number:</u>	UN 1139
<u>14.2. UN proper shipping name:</u>	Coating solution

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Steinschlag-Unterbodenschutz hellgrau 1l

Print date: 02.07.2020

Product code: 5550018

Page 9 of 10

14.3. Transport hazard class(es): 3**14.4. Packing group:** II

Hazard label: 3



Special Provisions: -

Limited quantity: 5 L

Excepted quantity: E2

EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number:** UN 1139**14.2. UN proper shipping name:** Coating solution**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3



Special Provisions: A3

Limited quantity Passenger: 1 L

Passenger LQ: Y341

Excepted quantity: E2

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: Hydrocarbons

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC): 53 %

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Steinschlag-Unterbodenschutz hellgrau 1l

Print date: 02.07.2020

Product code: 5550018

Page 10 of 10

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	SU main	SU	PC	PROC	ERC	AC	Specification
1	SU21 Consumer uses: Private households (= general public = consumers)	21	21	-	-	-	-	
2	PC9a Beschichtungen und Farben, Verdünner, Farbeentferner	-	-	9a	-	-	-	

SU main: Main user groups

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)