

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Jump start spray 400 ml

Revision date: 28.08.2019

Product code: 5570288

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

JMC Jump start spray 400 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name: Johannes J. Matthies GmbH & Co. KG
Street: Hammerbrookstr. 97
Place: D-20097 Hamburg
Telephone: + 49 (0) 40 2 37 21-0
e-mail: info@matthies.de
Internet: www.matthies.de

Supplier

Company name: Larsson UK Ltd.
Street: 7 Alpha Court, Phoenix Parkway
Place: GB-NN17 5DP Corby
Telephone: + 44 1536 265633
e-mail: info@larsson.uk.com
Internet: www.larsson.uk.com

1.4. Emergency telephone number: + 44 1536 265633**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:
Aerosol: Aerosol 1
Aspiration hazard: Asp. Tox. 1
Skin corrosion/irritation: Skin Irrit. 2
Serious eye damage/eye irritation: Eye Irrit. 2
Specific target organ toxicity - single exposure: STOT SE 3
Hazardous to the aquatic environment: Aquatic Chronic 3
Hazard Statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

acetone; propan-2-one; propanone
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, < 5% n-hexane
Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Jump start spray 400 ml

Revision date: 28.08.2019

Product code: 5570288

Page 2 of 15

Pictograms:**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe @ES04.B002074.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of waste according to applicable legislation.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Jump start spray 400 ml

Revision date: 28.08.2019

Product code: 5570288

Page 3 of 15

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane			20 - < 25 %
	216-653-1	603-181-00-X		
	Flam. Liq. 2, Skin Irrit. 2; H225 H315			
67-64-1	acetone; propan-2-one; propanone			5 - < 10 %
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, < 5% n-hexane			5 - < 10 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics			5 - < 10 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
67-56-1	methanol			0,1 - < 1 %
	200-659-6	603-001-00-X		
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Wash with plenty of soap and water. Take off immediately all contaminated clothing and wash it before reuse. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Jump start spray 400 ml

Revision date: 28.08.2019

Product code: 5570288

Page 4 of 15

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, Nausea, Dizziness, fatigue, Skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water mist. Foam0 Carbon dioxide (CO2)0 Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Gases of varying toxicity can be created through incomplete combustion and thermolysis. In the case of hydrocarbonic products (e.g. CO, CO₂, aldehydes and soot). These can be extremely hazardous if inhaled in high concentrations or enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use. Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Personal protection equipment: see section 8

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Jump start spray 400 ml

Revision date: 28.08.2019

Product code: 5570288

Page 5 of 15

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Avoid contact with skin. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Observe statutory rules and regulations.

Hints on joint storage

Do not store together with: Oxidizing agent0 Pyrophoric or self-heating substances0 Food and feedingstuffs

Further information on storage conditions

Protect against: Frost. Protect against direct sunlight. Store in a cool dry place. Observe statutory rules and regulations.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL
1634-04-4	Methyl-tert-butyl ether	50	183,5		TWA (8 h)	WEL
		100	367		STEL (15 min)	WEL

Additional advice on limit values

- a no restriction
- b End of exposure or shift
- c in long-term exposure: after several shifts
- d prior to next shift

Y: A risk of reproductive effects needs not to be feared if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

Z: A risk of reproductive effects cannot to be excluded if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

U: Urea

B: blood

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Jump start spray 400 ml

Revision date: 28.08.2019

Product code: 5570288

Page 6 of 15

Eye/face protection

Suitable eye protection: Wear safety glasses.
DIN EN 166

Hand protection

Apply skin protection cream for preventive skin protection.
When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Suitable material: NBR (Nitrile rubber).
Breakthrough time (maximum wearing time): 480 min
Thickness of the glove material: 0,45 mm
DIN EN 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Respiratory protection necessary at: exceeding exposure limit values
Suitable respiratory protection apparatus: gas filtering equipment (EN 141).
Filtering device with filter or ventilator filtering device of type: AX
Observe the wear time limits as specified by the manufacturer.
Observe statutory rules and regulations.

Environmental exposure controls

Observe statutory rules and regulations.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	colourless
Odour:	Solvent

pH-Value (at 20 °C):

Test method

DIN 19268

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	-40 °C
Flash point:	-80 °C

Flammability

Solid:	not applicable
Gas:	not applicable
Lower explosion limits:	1 vol. %
Upper explosion limits:	11 vol. %

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined

Oxidizing properties

Not oxidising.	
Vapour pressure:	not determined

Density (at 20 °C):	0,7429 g/cm ³ DIN 51757
---------------------	------------------------------------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Jump start spray 400 ml

Revision date: 28.08.2019

Product code: 5570288

Page 7 of 15

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents
not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

Data apply to the technically active substance.:Relative density, Colour, Odour, Viscosity, pH

SECTION 10: Stability and reactivity**10.1. Reactivity**

Flammable, Ignition hazard.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances

10.6. Hazardous decomposition products

Gases of varying toxicity can be created through incomplete combustion and thermolysis. In the case of hydrocarbonic products (e.g. CO, CO₂, aldehydes and soot). These can be extremely hazardous if inhaled in high concentrations or enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Jump start spray 400 ml

Revision date: 28.08.2019

Product code: 5570288

Page 8 of 15

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
75-28-5	isobutane				
	inhalation vapour	LC50 1237 mg/l	Mouse		
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane				
	oral	LD50 3866 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 85 mg/l	Rat		
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 5800 mg/kg	Rat		
	dermal	LD50 20000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, < 5% n-hexane				
	oral	LD50 >5000 mg/kg	Rat	Manufacturer	
	dermal	LD50 > 2800-3100 mg/kg	Rabbit	Manufacturer	Study report (1977)
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat	Manufacturer	Study report (1988)
64742-49-0	Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics				
	oral	LD50 5500 mg/kg	Rat	Manufacturer	
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Manufacturer	
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	Manufacturer	
106-97-8	butane				
	inhalation (4 h) gas	LC50 658 ppm	Rat	GESTIS	
67-56-1	methanol				
	oral	LD50 6000 mg/kg	Affe		
	dermal	LD50 17100 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 128,2 mg/l	Rat		Study report (1980)
	inhalation aerosol	ATE 0,5 mg/l			

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Jump start spray 400 ml

Revision date: 28.08.2019

Product code: 5570288

Page 9 of 15

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Jump start spray 400 ml

Revision date: 28.08.2019

Product code: 5570288

Page 10 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
75-28-5	isobutane					
	Acute fish toxicity	LC50 mg/l	91,42	96 h	Piscis	US EPA
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	US EPA OPPT
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	US EPA OPPT
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane					
	Acute fish toxicity	LC50	672 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 mg/l	> 800	72 h	Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50	651 mg/l	48 h	Daphnia magna (Big water flea)	
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Oncorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna	
74-98-6	propane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Piscis	US EPA
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	US EPA OPPT
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	US EPA OPPT
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, < 5% n-hexane					
	Acute fish toxicity	LC50 mg/l	> 1 - 10	96 h	Pimephales promelas (fathead minnow)	Manufacturer
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Pseudokirchneriella subcapitata	Manufacturer
	Acute crustacea toxicity	EC50 mg/l	> 1 - 10	48 h	Daphnia magna (Big water flea)	Manufacturer
	Fish toxicity	NOEC mg/l	2,045	28 d	Oncorhynchus mykiss (Rainbow trout)	Manufacturer CONCAWE, 2010
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna (Big water flea)	Manufacturer SIDS IARF SIAM
64742-49-0	Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics					
	Acute fish toxicity	LC50 mg/l	> 1 - 10	96 h	Oncorhynchus mykiss (Rainbow trout)	Manufacturer
	Acute algae toxicity	ErC50	12 mg/l	72 h	Pseudokirchneriella subcapitata	Manufacturer SIDS IARF SIAM
	Acute crustacea toxicity	EC50 mg/l	> 1 - 10	48 h	Daphnia magna (Big water flea)	Manufacturer
	Fish toxicity	NOEC mg/l	1,534	28 d	Oncorhynchus mykiss (Rainbow trout)	Manufacturer CONCAWE, (2010)
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna (Big water flea)	Manufacturer SIDS IARF SIAM
106-97-8	butane					

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Jump start spray 400 ml

Revision date: 28.08.2019

Product code: 5570288

Page 11 of 15

	Acute fish toxicity	LC50 mg/l	49,9	96 h	Piscis	US EPA	
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	US EPA OPPT	
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia Spec.	US EPA OPPT	
67-56-1	methanol						
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	
	Acute algae toxicity	ErC50 mg/l	ca. 220000	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna (Big water flea)	Water Research 23(4): 495-499 (1989)	
	Fish toxicity	NOEC mg/l	446,7	28 d	Pimephales promelas (fathead minnow)	SAR and QSAR in Environmental Research	
	Crustacea toxicity	NOEC	208 mg/l	21 d	Daphnia magna (Big water flea)	OECD QSAR Toolbox Report (2013)	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, < 5% n-hexane			
	OECD 301F	98 %	28	Manufacturer
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane	0,94
67-64-1	acetone; propan-2-one; propanone	-0,24
74-98-6	propane	1,09
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, < 5% n-hexane	3,4 - 5,2
106-97-8	butane	1,09
67-56-1	methanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
67-56-1	methanol	1	Cyprinus carpio (Common Carp)	Comparative Biochemi

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Jump start spray 400 ml

Revision date: 28.08.2019

Product code: 5570288

Page 12 of 15

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 2
 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Revision date: 28.08.2019	JMC Jump start spray 400 ml	Product code: 5570288
		Page 13 of 15

Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: See SP277
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC): EU 94,6 CH 71,7

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)
 Aerosol directive (75/324/EEC).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Jump start spray 400 ml

Revision date: 28.08.2019

Product code: 5570288

Page 14 of 15

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

VwVwS: Verwaltungsvorschrift wassergefährdende Stoffe (17. Mai 1999)

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H370 Causes damage to organs.

H411 Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Jump start spray 400 ml

Revision date: 28.08.2019

Product code: 5570288

Page 15 of 15

H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)