


SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** **OEM TWIN AIR BIO LIQUID POWER**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Air filter oil
Only for proper handling.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MOTOREX AG
Bern-Zürich-Strasse 31, Postfach
CH-4901 Langenthal
Tel. +41 (0)62 919 75 75
www.motorex.com
- **Further information obtainable from:** msds@motorex.com
- **1.4 Emergency telephone number:**
In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**


GHS02 GHS07 GHS08 GHS09
- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
Hydrocarbons, C6, isoalkanes, <5% of n-hexane
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2021

Version number 2.1

Revision: 19.04.2021

Trade name: OEM TWIN AIR BIO LIQUID POWER

(Contd. of page 1)

- P103 Read carefully and follow all instructions.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P321 Specific treatment (see on this label).
- P331 Do NOT induce vomiting.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	≥20-<25%
EC number: 931-254-9 Reg.nr.: 01-2119484651-34	Hydrocarbons, C6, isoalkanes, <5% of n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	≥10-<20%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2021

Version number 2.1

Revision: 19.04.2021

Trade name: OEM TWIN AIR BIO LIQUID POWER

(Contd. of page 2)

- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see section 7.
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

Hydrocarbons, C6, isoalkanes, <5% of n-hexane

Oral	DNEL/general population/Systemic effects/Long-term	1,301 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-term	13,964 mg/kg/24h (worker)
	DNEL/general population/Systemic effects/Long-term	1,377 mg/kg/24h (consumer)
Inhalative	DNEL / Workers / Systemic effects / Long-term	5,306 mg/m3 (worker)
	DNEL/general population/Systemic effects/Long-term	1,131 mg/m3 (consumer)

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2021

Version number 2.1

Revision: 19.04.2021

Trade name: OEM TWIN AIR BIO LIQUID POWER

(Contd. of page 3)

- **Additional information:** *The lists valid during the making were used as basis.*
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
*Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.*
- **Respiratory protection:**
*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
 Not necessary if room is well-ventilated.
 Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.*
- **Protection of hands:**



Protective gloves

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



safety goggles

- **Body protection:** *Protective work clothing*

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Fluid
Colour:	Dark green
Odour:	Solvent-like
Odour threshold:	Not determined.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	65 °C (DIN EN ISO 3405)
- **Flash point:** <-20 °C

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2021

Version number 2.1

Revision: 19.04.2021

Trade name: OEM TWIN AIR BIO LIQUID POWER

(Contd. of page 4)

· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	250 °C (DIN 51794)
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1 Vol %
Upper:	7.3 Vol %
· Vapour pressure at 20 °C:	1.9 hPa
· Density at 20 °C:	0.781 g/cm ³ (ASTM D 4052)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	7.1 mm ² /s @ 40 °C
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Hydrocarbons, C6, isoalkanes, <5% of n-hexane		
Oral	LD50	25 ml/kg (rat)
Dermal	LD50	5 ml/kg (rabbit)
Inhalative	LC50 / 4h	73,860 ppm (rat)
	NOAEC	8,992 ppm (mouse)
	LOAEC	2,984-8,992 ppm (rat)
	LOAEC	8,992 ppm (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2021

Version number 2.1

Revision: 19.04.2021

Trade name: OEM TWIN AIR BIO LIQUID POWER

(Contd. of page 5)

- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Hydrocarbons, C6, isoalkanes, <5% of n-hexane

LL50	18.27 mg/l/96h (fish)
EL50	31.9 mg/l/48h (aquatic invertebrates)
EL50	13.56 mg/l/72h (algae / cyanobacteria)
NOELR	4.089 mg/l/28d (fish)
NOELR	7.138 mg/l/21d (aquatic invertebrates)
NOELR	3.034 mg/l/72h (algae / cyanobacteria)

- **12.2 Persistence and degradability** No further relevant information available.

12.3 Bioaccumulative potential

Hydrocarbons, C6, isoalkanes, <5% of n-hexane

Partition coefficient	3.6 [---] (log Kow) (Bioaccumulation)
Biodegradability	>80 % (28d) (Biodegradability) (OECD 301 F)

- **12.4 Mobility in soil** No further relevant information available.

Ecotoxicological effects:

· **Remark:** Toxic for fish

Additional ecological information:

General notes:

Water hazard class 2 (according to Appendix 1 AWSV): significantly hazardous to water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2021

Version number 2.1






Revision: 19.04.2021

Trade name: OEM TWIN AIR BIO LIQUID POWER

(Contd. of page 6)

- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Discharged containers can contain flammable or explosive vapours.

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN-Number · ADR/RID/ADN, IMDG, IATA 	UN3295	
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR/RID/ADN · IMDG · IATA 	3295 HYDROCARBONS, LIQUID, N.O.S., ENVIRONMENTALLY HAZARDOUS HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% n-hexane), MARINE POLLUTANT HYDROCARBONS, LIQUID, N.O.S.	
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR/RID/ADN 	<div style="display: flex; align-items: center; gap: 10px;">   </div> <ul style="list-style-type: none"> · Class · Label 	3 (F1) Flammable liquids. 3
<ul style="list-style-type: none"> · IMDG 	<div style="display: flex; align-items: center; gap: 10px;">   </div> <ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids. 3
<ul style="list-style-type: none"> · IATA 	<div style="display: flex; align-items: center; gap: 10px;">  </div> <ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids. 3
<ul style="list-style-type: none"> · 14.4 Packing group · ADR/RID/ADN, IMDG, IATA 	II	
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR/RID/ADN): 	Product contains environmentally hazardous substances: Hydrocarbons C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% n-hexane Symbol (fish and tree) Symbol (fish and tree)	
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 	Warning: Flammable liquids. 33 F-E,S-D B	

(Contd. on page 8)

CB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2021

Version number 2.1

Revision: 19.04.2021

Trade name: OEM TWIN AIR BIO LIQUID POWER

(Contd. of page 7)

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 3295 HYDROCARBONS, LIQUID, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

- **purity requirement**
- **Relevant phrases**
H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
- **Department issuing SDS:** Abteilung Produktsicherheit
- **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2021

Version number 2.1

Revision: 19.04.2021

Trade name: OEM TWIN AIR BIO LIQUID POWER

(Contd. of page 8)

CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids – Category 2
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 · *** Data compared to the previous version altered.**

Annex: Exposure scenario 1

- **Short title of the exposure scenario**
Industrial use of lubricants and greases in vehicles or machinery
- **Sector of Use**
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category**
 - PC16 Heat transfer fluids*
 - PC17 Hydraulic fluids*
 - PC24 Lubricants, greases, release products*
- **Process category**
 - PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.*
 - PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions*
 - PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities*
 - PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)*
- **Environmental release category**
 - ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)*
 - ERC7 Use of functional fluid at industrial site*
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** *5 workdays/week.*
- **Physical parameters**
- **Physical state** *Fluid*
- **Concentration of the substance in the mixture** *The substance is main component.*
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** *No special measures required.*
- **Other operational conditions affecting consumer exposure** *Not required.*
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** *No special measures required.*
- **Technical protective measures** *No special measures required.*
- **Personal protective measures** *No special measures required.*
- **Measures for consumer protection** *No special measures required.*
- **Environmental protection measures**
- **Air** *No special measures required.*
- **Water** *No special measures required.*
- **Disposal measures** *Ensure that waste is collected and contained.*
- **Disposal procedures** *Dispose of product residues with household waste.*
- **Waste type** *Partially emptied and uncleaned packaging*
- **Exposure estimation**
- **Consumer** *Not relevant for this Exposure Scenario.*

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2021

Version number 2.1

Revision: 19.04.2021

Trade name: OEM TWIN AIR BIO LIQUID POWER

(Contd. of page 9)

- **Guidance for downstream users** No further relevant information available.

Annex: Exposure scenario 2

- **Short title of the exposure scenario**
Professional use of lubricants and greases in vehicles or machines
- **Sector of Use**
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category**
PC16 Heat transfer fluids
PC17 Hydraulic fluids
PC24 Lubricants, greases, release products
- **Process category**
PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC20 Use of functional fluids in small devices
- **Environmental release category**
ERC9a Widespread use of functional fluid (indoor)
ERC9b Widespread use of functional fluid (outdoor)
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** *5 workdays/week.*
- **Physical parameters**
- **Physical state** *Fluid*
- **Concentration of the substance in the mixture** *The substance is main component.*
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** *No special measures required.*
- **Other operational conditions affecting consumer exposure** *Not required.*
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** *No special measures required.*
- **Technical protective measures** *No special measures required.*
- **Personal protective measures** *No special measures required.*
- **Measures for consumer protection** *No special measures required.*
- **Environmental protection measures**
- **Air** *No special measures required.*
- **Water** *No special measures required.*
- **Disposal measures** *Ensure that waste is collected and contained.*
- **Disposal procedures** *Dispose of product residues with household waste.*
- **Waste type** *Partially emptied and uncleaned packaging*
- **Exposure estimation**
- **Consumer** *Not relevant for this Exposure Scenario.*
- **Guidance for downstream users** *No further relevant information available.*

Annex: Exposure scenario 3

- **Short title of the exposure scenario** *Private use of lubricants and greases in vehicles or machines*
- **Sector of Use** *SU21 Consumer uses: Private households / general public / consumers*
- **Product category** *PC24 Lubricants, greases, release products*

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.04.2021

Version number 2.1

Revision: 19.04.2021

Trade name: OEM TWIN AIR BIO LIQUID POWER

(Contd. of page 10)

- **Environmental release category**
- ERC9a Widespread use of functional fluid (indoor)
- ERC9b Widespread use of functional fluid (outdoor)
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting consumer exposure** Not required.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures** No special measures required.
- **Personal protective measures** No special measures required.
- **Measures for consumer protection** No special measures required.
- **Environmental protection measures**
- **Air** No special measures required.
- **Water** No special measures required.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures** Dispose of product residues with household waste.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.

GB