



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Product code : 908825

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global
Operations
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local
CSR contact person

E-mail address of person : SDS@valvolineglobal.com
responsible for the SDS

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865

, or contact your local emergency telephone number at 0 30-1 92 40

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard,
Category 3

H412: Harmful to aquatic life with long lasting
effects.



SAFETY DATA SHEET
 according to Regulation (EC) No. 1907/2006
 Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
 Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
 P273 Avoid release to the environment.

Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- xxxx	Asp. Tox. 1; H304	>= 25 - < 40
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8 265-158-7 649-468-00-3 01-2119487077-29- xxxx	Asp. Tox. 1; H304	>= 2,5 - < 5



ValvolineTM
Global

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
ValvolineTM HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0 265-169-7 649-474-00-6 01-2119471299-27- XXXX	Asp. Tox. 1; H304	>= 2,5 - < 5
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4 01-2119488911-28- XXXX	Aquatic Chronic 4; H413	>= 1 - < 2,5
PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3- DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS	84605-29-8 283-392-8 01-2119493626-26- XXXX	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 2; H411 specific concentration limit Skin Irrit. 2; H315 >= 6,25 % Eye Dam. 1; H318 >= 12,5 % Eye Irrit. 2; H319 >= 10,0 %	>= 1 - < 2,5
Branched alkylphenol and Calcium branched alkylphenol	74499-35-7 604-092-00-9	Skin Corr. 1C; H314 Eye Dam. 1; H318 Repr. 1B; H360F Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10	>= 0,025 - < 0,1
Substances with a workplace exposure limit :			
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8		>= 40 - < 50
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- XXXX		>= 5 - < 10



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | | |
|-------------------------|---|---|
| General advice | : | Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended. |
| If inhaled | : | If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician. |
| In case of skin contact | : | If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : | Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : | Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|----------|---|--------------------------------|
| Symptoms | : | No symptoms known or expected. |
|----------|---|--------------------------------|

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|--|
| Treatment | : | No hazards which require special first aid measures.

Treat symptomatically. |
|-----------|---|--|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|------------------------------|---|--|
| Suitable extinguishing media | : | Use water spray, alcohol-resistant foam, dry chemical or |
|------------------------------|---|--|



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

carbon dioxide.
Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : carbon dioxide and carbon monoxide
Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage



SAFETY DATA SHEET
 according to Regulation (EC) No. 1907/2006
 Valvoline™ HYBRID VEHICLE C3 5W/30 4/5 L
 Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours/dust.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : When using do not eat or drink. When using do not smoke.
 Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
- Storage class (TRGS 510) : 10
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	AGW (Vapour and aerosols)	5 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category): 4;(II)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				



ValvolineTM
Global

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
ValvolineTM HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	AGW (Vapour and aerosols)	5 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	AGW (Vapour and aerosols)	5 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	AGW (Vapour and aerosols)	5 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	AGW (Vapour and aerosols)	5 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS	84605-29-8	MAK (Inhalable fraction.)	2 mg/m ³	DFG MAK
	Peak-limit: excursion factor (category): 2			
		MAK (Respirable fraction.)	0,1 mg/m ³	DFG MAK
	Peak-limit: excursion factor (category): 4			



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection
Material : neoprene, nitrile rubber
Break through time : ≥ 240 min
Glove thickness : $\geq 0,35$ mm
Directive : Equipment should conform to EN 374

Remarks : The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : amber
Odour : oily
Odour Threshold : No data available

Melting point/freezing point : No data available



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

Boiling point/boiling range	:	No data available
Flammability	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	ca. 203,5 °C Method: Pensky-Martens closed cup
Decomposition temperature	:	No data available
pH	:	Not applicable
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. 74,8 mm ² /s (40 °C)
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	No data available
Relative density	:	No data available
Density	:	ca. 0,8495 g/cm ³ (15,6 °C)
Relative vapour density	:	No data available

9.2 Other information

Oxidizing properties	:	No data available
Self-ignition	:	No data available
Evaporation rate	:	No data available



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : excessive heat
Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents
strong reducing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

- Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: No mortality observed at this dose.
- Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: The toxicological data has been taken from products of similar composition.

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

- Acute inhalation toxicity : LC50 (Rat): > 2,3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

- Acute oral toxicity : LD50 (Rat): > 15 g/kg
- Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

- Acute oral toxicity : LD50 (Rat): > 15 g/kg
- Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

- Remarks : May cause skin irritation and/or dermatitis.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

Assessment : Slight, transient irritation
Result : Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Rabbit
Result : Mild skin irritation
Remarks : The toxicological data has been taken from products of similar composition.

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Species : Rabbit
Result : Irritating to skin.

Branched alkylphenol and Calcium branched alkylphenol:

Result : No skin irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : May cause irreversible eye damage.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : No eye irritation
Result : No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Rabbit
Result : Slight, transient irritation
Remarks : The toxicological data has been taken from products of similar composition.

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Species : Rabbit
Result : Corrosive

Branched alkylphenol and Calcium branched alkylphenol:

Result : Irritating to eyes.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : No eye irritation
Result : No eye irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : No eye irritation
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

Respiratory sensitisation

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Remarks : The toxicological data has been taken from products of similar composition.

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

Components:

Branched alkylphenol and Calcium branched alkylphenol:

Reproductive toxicity - : Clear evidence of adverse effects on sexual function and
Assessment fertility, based on animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Components:

Branched alkylphenol and Calcium branched alkylphenol:

Assessment : The substance is considered to have endocrine disrupting properties according to REACH Article 57(f) for human health.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10.000 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC: 10 mg/l
Species: Fish

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Species: Aquatic invertebrates

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Remarks: The toxicological data has been taken from products of similar composition.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,4 mg/l
End point: Reproduction Test
Exposure time: 28 d
Species: Daphnia magna (Water flea)
Test substance: WAF
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Branched alkylphenol and Calcium branched alkylphenol:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Acute aquatic toxicity Category 1; Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Chronic aquatic toxicity Category 1; Very toxic to aquatic life with long lasting effects.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10.000 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC: 10 mg/l
Species: Fish

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Species: Aquatic invertebrates

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

12.2 Persistence and degradability

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1,5 %
Exposure time: 28 d
Method: OECD Test Guideline 301B



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

12.3 Bioaccumulative potential

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Partition coefficient: n- : log Pow: > 7,5
octanol/water

**PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS,
ZINC SALTS:**

Partition coefficient: n- : log Pow: 0,56
octanol/water

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n- : log Pow: Expected > 7
octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Components:

Branched alkylphenol and Calcium branched alkylphenol:

Assessment : The substance is considered to have endocrine disrupting properties according to REACH Article 57(f) for the environment.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA_P : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA_P : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA_P : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA_P (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable
REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. 34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Water hazard class (Germany) : WGK 1 slightly hazardous to water
TA Luft List (Germany) : 5.2.1: Total dust: Not applicable
5.2.2: Inorganic substances in powdered form: Not applicable
5.2.4: Inorganic substances in gaseous form: Not applicable
5.2.5: Organic Substances:
Class 1: 48,2 % DIPHENYLAMINE, DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC, HYDROTREATED LIGHT PARAFFINIC DISTILLATE, DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC, PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS, DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC, Branched alkylphenol and Calcium branched alkylphenol
5.2.7.1.1: Carcinogenic substance: Not applicable
5.2.7.1.1: Quartz fine dust PM4: Not applicable
5.2.7.1.1: Formaldehyde: Not applicable
5.2.7.1.1: fibres: Not applicable
5.2.7.1.2: Germ cell mutagens:



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

Not applicable
5.2.7.1.3: Substances toxic to reproduction:
others: 0,04 % Branched alkylphenol and Calcium branched
alkylphenol
5.2.7.2: Poorly degradable, easily enrichable and highly toxic
organic substances:
Not applicable

The components of this product are reported in the following inventories:

TCSI	:	On the inventory, or in compliance with the inventory
TSCA	:	All substances listed as active on the TSCA inventory
AiIC	:	Not in compliance with the inventory
DSL	:	All components of this product are on the Canadian DSL
ENCS	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
NZIoC	:	Not in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AiIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements

H304	:	May be fatal if swallowed and enters airways.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H318	:	Causes serious eye damage.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

H360F	:	May damage fertility.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Repr.	:	Reproductive toxicity
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
DFG MAK	:	Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DF
DE TRGS 900 / AGW	:	Time Weighted Average
DFG MAK / MAK	:	Maximum allowable concentration:

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration,



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ HYBRID VEHICLE C3 5W30 4/5 L
Synthetic Motor Oil

Version: 4.0

Revision Date: 11.07.2023

Print Date: 14/08/2025

Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Internal information : 000000277159

Classification of the mixture:

Aquatic Chronic 3 H412

Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN