



Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 03.05.2016

Version: 2

Revision: 03.05.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Muc-Off Endurance Chain Lube
- **Article number:** 637
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU21 Consumer uses: Private households / general public / consumers
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC24 Lubricants, greases, release products
- **Process category**
 PROC7 Industrial spraying
 PROC11 Non industrial spraying
- **Application of the substance / the mixture** Lubricant
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Muc-Off Ltd
 Unit 1, 1st Floor, Concept Office Park
 Innovation Close, Poole, Dorset, BH12 4QT
 Tel: +44 (0) 1202 307790
 Fax: +44 (0) 1202 746853
 E-mail: info@muc-off.com
- **Further information obtainable from:** Research & Development/E-mail: info@muc-off.com
- **1.4 Emergency telephone number:** During normal opening hours: Tel +44 (0) 1202 307790

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS07



GHS09

- **Signal word** Danger

(Contd. on page 2)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 03.05.2016

Version: 2

Revision: 03.05.2016

Trade name: Muc-Off Endurance Chain Lube

(Contd. of page 1)

· Hazard-determining components of labelling:

Pentane

Distillates (petroleum), hydrotreated heavy paraffinic benzene < 0.1%

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves / eye protection.

P273 Avoid release to the environment.

P271 Use only outdoors or in a well-ventilated area.

P301+P310 IF SWALLOWED: Immediately call a doctor.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P331 Do NOT induce vomiting.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients
· 3.2 Mixtures
· Description: Active substance with propellant

· Dangerous components:

| | | |
|---|---|---------|
| CAS: 109-66-0 EINECS: 203-692-4 Reg.nr.: 01-2119459286-30 | Pentane Flam. Liq. 1, H224; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336 | 25-<50% |
| CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32 | butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas C, H280 | 10-<25% |
| CAS: 64742-54-7 EINECS: 265-157-1 | Distillates (petroleum), hydrotreated heavy paraffinic benzene < 0.1% Asp. Tox. 1, H304 | 10-<25% |
| CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21 | propane Flam. Gas 1, H220; Press. Gas C, H280 | 10-<25% |

· Ingredients according to detergents guideline 648/2004/EC

| | |
|------------------------|-------|
| aliphatic hydrocarbons | ≥ 30% |
|------------------------|-------|

· Additional information:

GB

(Contd. on page 3)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 03.05.2016

Version: 2

Revision: 03.05.2016

Trade name: Muc-Off Endurance Chain Lube

(Contd. of page 2)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

GB

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 03.05.2016

Version: 2

Revision: 03.05.2016

Trade name: Muc-Off Endurance Chain Lube

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:**
Observe official regulations on storing packagings with pressurised containers.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

109-66-0 Pentane

WEL Long-term value: 1800 mg/m³, 600 ppm

106-97-8 butane (containing < 0.1% butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

74-98-6 propane

OEL Short-term value: 3600 mg/m³, 2000 ppm
Long-term value: 1800 mg/m³, 1000 ppm

DNELs

109-66-0 Pentane

| | | |
|------------|-------------------------|---|
| Oral | DNEL Long term-systemic | 214 mg/kg bw/day (Consumer) |
| Dermal | DNEL Long term-systemic | 214 mg/kg bw/day (Consumer) 432 mg/kg bw/day (Worker) |
| Inhalative | DNEL Long term-systemic | 643 mg/m ³ (Consumer) 3000 mg/m ³ (Worker) |

- **Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

Protection of hands:

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

(Contd. on page 5)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 03.05.2016

Version: 2

Revision: 03.05.2016

Trade name: Muc-Off Endurance Chain Lube

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm
Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Safety glasses



Tightly sealed goggles

Body protection: Use protective suit. (EN-13034/6)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
General Information
Appearance:

| | |
|-------------------------|-----------------|
| Form: | Aerosol |
| Colour: | Light brown |
| Odour: | Sweetish |
| Odour threshold: | Not determined. |

pH-value: Not determined.

Change in condition

| | |
|-------------------------------------|---------------|
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | -44 °C |

Flash point: -97 °C

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 285 °C

Decomposition temperature: Not determined.

Self-igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

| | |
|---------------|------------|
| Lower: | 1.4 Vol % |
| Upper: | 10.9 Vol % |

Vapour pressure at 20 °C: 8300 hPa

Density at 20 °C: 0.649 g/cm³

(Contd. on page 6)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 03.05.2016

Version: 2

Revision: 03.05.2016

Trade name: Muc-Off Endurance Chain Lube

(Contd. of page 5)

| | |
|---|--|
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not applicable. |
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 73.6 % |
| Solids content: | 0.4 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

109-66-0 Pentane

| | |
|------------|---|
| NOEC (72h) | 7.51 mg/l (Pseudokirchneriella subcapitata) |
| EC50 (72h) | 10.7 mg/l (Pseudokirchneriella subcapitata) |
| LC50/96h | 4.26 mg/l (Oncorhynchus mykiss (96h)) |

(Contd. on page 7)

GB

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 03.05.2016

Version: 2

Revision: 03.05.2016

Trade name: Muc-Off Endurance Chain Lube

(Contd. of page 6)



| | |
|----------|--------------------------|
| EC50/48h | 2.7 mg/l (Daphnia magna) |
|----------|--------------------------|

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
 Water danger class 3 (German Regulation) (Self-assessment): extremely hazardous for water
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 Danger to drinking water if even extremely small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, ADN, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR, ADN** UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
- **IMDG** AEROSOLS (PENTANES, Zinc naphthenate), MARINE POLLUTANT
- **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR**
- | | | |
|---|---|--|
|  |  | |
|---|---|--|
- **Class** 2 5F Gases.
- **Label** 2.1
- **ADN**
- **ADN/R Class:** 2 5F

(Contd. on page 8)

GB

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 03.05.2016

Version: 2

Revision: 03.05.2016

Trade name: Muc-Off Endurance Chain Lube

(Contd. of page 7)

· **IMDG**

· **Class** 2.1
 · **Label** 2.1

· **IATA**

· **Class** 2.1
 · **Label** 2.1

· **14.4 Packing group**

· **ADR, IMDG, IATA** Void

· **14.5 Environmental hazards:**

Product contains environmentally hazardous substances:
 Pentane

· **Marine pollutant:**

Yes
 Symbol (fish and tree)

· **Special marking (ADR):**

Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Gases.

· **Danger code (Kemler):**

-

· **EMS Number:**

F-D,S-U

· **Stowage Code**

SW1 Protected from sources of heat.
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **ADR**

· **Limited quantities (LQ)** 1L

· **Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

· **Transport category**

2

· **Tunnel restriction code**

D

· **IMDG**

· **Limited quantities (LQ)** 1L

· **Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

(Contd. on page 9)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 03.05.2016

Version: 2

Revision: 03.05.2016

Trade name: Muc-Off Endurance Chain Lube

(Contd. of page 8)

· **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 28, 29, 30

· **National regulations:**

| Class | Share in % |
|-------|------------|
| NK | 50-<75 |

- **VOC-CH** 73.59 %
- **VOC-EU** 477.6 g/l
- **Danish MAL Code** 5-3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H224 Extremely flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
- DNEL: Derived No-Effect Level (REACH)
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- SVHC: Substances of Very High Concern
- Flam. Gas 1: Flammable gases – Category 1
- Aerosol 1: Aerosols – Category 1
- Press. Gas C: Gases under pressure – Compressed gas
- Flam. Liq. 1: Flammable liquids – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 10)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 03.05.2016

Version: 2

Revision: 03.05.2016

Trade name: Muc-Off Endurance Chain Lube

(Contd. of page 9)

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered. ***

GB